



## Approval of the Trademark Trevira CS®

Gabriel A/S  
Hjulgagervej 55  
9000 Aalborg  
Denmark

<b>Application No.:</b>	240043.1
<b>Date of issue:</b>	27.02.2024
<b>Valid until:</b>	26.02.2029
<b>Article name:</b>	Go Uni
<b>End use:</b>	Drapes Upholstery fabrics
<b>Square weight (g/m<sup>2</sup>):</b>	310
According to customer specification	
<b>Composition of the raw materials:</b>	Polyester 100%
<b>Composition of the fabric:</b>	Trevira CS 100%

The article Go Uni col. 60999 has been tested under the Trevira trademark application no. 240043 and is granted approval for the trademark Trevira CS® for interior use.

The article was tested according to DIN 4102 part 1, 6.2 and thus also meets the requirements for fire class DIN 4102-B1.

The article was tested according to the French Standard NF P 92-504 (Propagation de flamme) and thus also meets the requirements for class M1 according to NF P 92-503, 92-505 and 92-507.

The article meets the requirements for class 1 according to EN 13773.

This article qualifies for class B-s1, d0 according to the European Standard EN 13501-1. Trevira CS has been approved by the DIBt with the General Building Inspectorate Approval, Approval No. Z-56.25-3573 dd. 10 January 2024.

Thus meets also the requirements for class 1 according to the Italian Standards UNI 8456 and UNI 8457.

This article also meets the requirements according to the North American standard NFPA 701: 2010 Test Method #1 (based on the Test Reports Govmark, New York No. 2-94779, 2-94780, 2-94781).

Thus meets also the requirements according to British Standard BS 5867 part 2 type C.

This article can meet the requirements according to ÖNORM A 3800-1 part 1, class B1, fume formation class Q 1 and droplet formation class TR1.

This article meets the requirements according to EN 1021-1 and -2:2014 in conjunction with polyurethan foams with a density of more than 30 kg/m<sup>3</sup>.

This article also meets the requirements for class I according to the North American standard NFPA 260 for upholstered furniture (based on the Test Reports no. 10-002-775 A + B dated 24.11.2010).

Thus meets also the requirements according to British Standard BS 5852: ignition source 0 (cigarette), ignition source 1 (match) and ignition source 5 (crib 5) in conjunction with suitable combustion modified foams (at least 50 kg/m<sup>3</sup>).

Thus meets also the requirements according to the Italian standard UNI 9175, class 1 IM in conjunction with suitable combustion modified foams.

Thus meets also the requirements according to ÖNORM B 3825 in conjunction with suitable combustion modified foams.

This article can meet the requirements according to FAR/JAR/CS 25.853 App. F to part 25, part I, § (a), (1) (ii) (vertical test, ignition time 12 sec).

Indorama Ventures Fibers Germany GmbH  
(This document is valid without signature.)

Indorama Ventures Fibers Germany GmbH, Trademark Service, Max-Fischer-Straße 11, 86399 Bobingen, Germany  
E-Mail: [trademarkservice.IVFG@de.indorama.net](mailto:trademarkservice.IVFG@de.indorama.net)