

Confidential Report

Our Ref: 23/58449-3-2





Telephone: +44 (0) 113 259 1999 Email: info@bttg.co.uk

: www.bttg.co.uk

Date: 28 April 2021

Our Ref: 23/58449-3-2

Your Ref: ---

Page: 1 of 4

Client: Gabriel A/S

Hjulmagerve 55 DK-900 Aalborg Denmark

Job Title: Fire Test on One Fabric Sample

Clients Order Ref: 0011530517

Date of Receipt: 14 April 2021

Date Test Started: 22 April 2021

Description of Sample: One sample of fabric, which was referenced by the client as;

Item Description: Athlon Plus 60140 L. Grey, Item Number: 650160140, stated

to be 56% PES, 44% Trevira CS

Work Requested: We were asked to test the received sample to the following standard:

BS EN 1021:Part 1:2014 - Ignitability of Upholstered Furniture



** subcontracted test, EN ISO/IEC 17025 accredited

*** not UKAS accredited

Note: This report relates only to the samples submitted and as described in the report.





Telephone: +44 (0) 113 259 1999

Email: <u>info@bttg.co.uk</u> : www.bttg.co.uk

Date: 28 April 2021

Our Ref: 23/58449-3-2 Your Ref: ---

Page: 2 of 4

Client: Gabriel A/S

FIRE TEST ACCORDING TO BS EN 1021-1:2014

Assessment of the ignitability of upholstered furniture. Part I. Ignition Source 0: Smouldering cigarette

Pre-Treatment

The sample did not have a flame retardant treatment therefore it was not subjected to a water soak pre-treatment

Conditioning

The sample was conditioned for at least 16 hours at a temperature of 23±2°C and relative humidity of 50±5%.

The sample was tested in a room of volume 25m³ and 17°C.

Procedure

The test was carried out in accordance with BS EN 1021-1:2014. The sponsor sampled the material and the specimens were cut from the sample received to the dimensions set out in the standard.

The sample was tested over non-fire retardant polyurethane foam with a density of approximately 20-22 kg/m³.

Tests were made using ignition source 0.

Requirements

The specimens shall not:-

Smouldering Criteria

- a) display escalating combustion requiring active extinction.
- b) smoulder or burn until it is essentially consumed within the test duration.
- c) smoulder or burn to the extremities of the specimen, or through the full thickness, within the duration of the test.
- d) smoulder for more than one hour.
- e) on final examination, show evidence of progressive smouldering.





Telephone: +44 (0) 113 259 1999

Email: <u>info@bttg.co.uk</u> : www.bttg.co.uk

Date: 28 April 2021

Our Ref: 23/58449-3-2 Your Ref: ---

Page: 3 of 4

Client: Gabriel A/S

Requirements (continued)

Flaming Criteria

a) show evidence of flaming initiated by a smouldering source.

Results

Smouldering criteria	Specimen No.	
	1	2
Placement of Cigarette	Flat	Flat
Unsafe escalating combustion	No	No
Testing assembly consumed	No	No
Smoulders to extremities/full thickness	No	No
Smoulders more than 1 hour	No	No
In final examination, presence of progressive	No	No
smouldering		
Flaming criteria	1	2
Occurrence of flames	No	No
Specimen Result	Ignition (I)	Ignition (1)
(Ignition or Non-ignition)	Ignition (I)	Ignition (I)

Any "Yes" in smouldering or flaming criteria means Ignition

Cigarette Test Result PASS

Note

The test results relate only to the ignitability of the combination of materials under the particular conditions of test; they are not intended as a means of assessing the full potential fire hazard of the materials in use.





Telephone: +44 (0) 113 259 1999

Email: <u>info@bttg.co.uk</u> : <u>www.bttg.co.uk</u>

Date: 28 April 2021

Our Ref: 23/58449-3-2 Your Ref: ---

Page: 4 of 4

Client: Gabriel A/S

Comments

An NI designation indicates the sample meets the performance requirements of BS EN 1021-1.

This report relates only to the samples submitted and as described in the report.

The overall uncertainty budget for BS EN 1021:Part 1:2014 is as follows:-

Timings: ±2 seconds.

Reported by:....

B Bland

Technical Customer Service Officer

Enquiries concerning this report should be addressed to Customer Services.

Countersigned By:.

P Doherty

Manager

